

60×60×25 mm

San Ace 60 9RA type



General Specifications

- Material Frame: Plastic (Flammability: UL 94V-0), Impeller: Plastic (Flammability: UL 94V-1)
- Expected life See the table below. (L10 life: 90% survival rate for continuous operation in free air at 60°C, rated voltage) Expected life at 40°C is for reference only.
- Motor protection function Locked rotor burnout protection, Reverse polarity protection
For details, please refer to p. 614.
- Dielectric strength 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)
- Insulation resistance 10 MΩ min. at 500 VDC (between lead wire conductors and frame)
- Sound pressure level (SPL) A-weighted sound pressure level (SPL) at 1 m away from the air inlet.
- Storage temperature -30 to +70°C (Non-condensing)
- Lead wire ⊕Red ⊖Black (Sensor) Yellow (Control) Brown
(For models without PWM control, there is no speed control wiring.)
- Mass 70 g

Specifications

The models listed below **have ribs and a pulse sensor with PWM control**. For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	PWM duty cycle [%]	Rated current [A]	Rated input [W]	Rated speed [min ⁻¹]	Max. airflow [m ³ /min] [CFM]	Max. static pressure [Pa] [inchH ₂ O]	SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
9RA0612P4J001	12	10.8 to 13.2	100	0.35	4.2	7700	1.1 38.8	130 0.52	41	-20 to +70	60000/60°C (90000/40°C)
			30	0.05	0.6	1900	0.27 9.5	8.1 0.03	13		
9RA0624P4J001	24	21.6 to 26.4	100	0.18	4.32	7700	1.1 38.8	130 0.52	41		
			20	0.03	0.72	1700	0.24 8.5	6.5 0.02	11		
9RA0648P4J001	48	43.2 to 52.8	100	0.1	4.8	7700	1.1 38.8	130 0.52	41		
			20	0.03	1.44	1800	0.25 8.8	7.1 0.03	12		

* PWM frequency is 25 kHz. Models without ratings for 0% PWM duty cycle have zero speed at 0%. When control terminal is open, speed is the same as at 100% duty cycle.

The models listed below **have ribs and a pulse sensor**. For models without ribs, append "1" to the end of model numbers.

Model no.	Rated voltage [V]	Operating voltage range [V]	Rated current [A]	Rated input [W]	Rated speed [min ⁻¹]	Max. airflow [m ³ /min] [CFM]	Max. static pressure [Pa] [inchH ₂ O]	SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
9RA0612J4001	12	7 to 13.8	0.35	4.2	7700	1.1 38.8	130 0.52	41	-20 to +70	60000/60°C (90000/40°C)
9RA0612G4001			0.15	1.8	5600	0.8 28.2	69 0.28	36		
9RA0612S4001			0.1	1.2	4600	0.66 23.3	46 0.18	30		
9RA0612H4001			0.07	0.84	3800	0.54 19.1	32 0.13	26		
9RA0612F4001		6 to 13.8	0.05	0.6	3200	0.46 16.2	22 0.09	21		
9RA0612M4001			0.04	0.48	2600	0.37 13	14.8 0.06	17		
9RA0624J4001	24	14 to 27.6	0.18	4.32	7700	1.1 38.8	130 0.52	41		
9RA0624G4001			0.08	1.92	5600	0.8 28.2	69 0.28	36		
9RA0624S4001			0.06	1.44	4600	0.66 23.3	46 0.18	30		
9RA0624H4001			0.05	1.2	3800	0.54 19.1	32 0.13	26		
9RA0624F4001		12 to 27.6	0.04	0.96	3200	0.46 16.2	22 0.09	21		
9RA0624M4001		14 to 27.6	0.03	0.72	2600	0.37 13	14.8 0.06	17		
9RA0648J4001	48	36 to 55.2	0.1	4.8	7700	1.1 38.8	130 0.52	41		
9RA0648G4001			0.06	2.88	5600	0.8 28.2	69 0.28	36		


Note 1: Sensor and control options are available for selection. Refer to the table on pp. 649 to 650.

Note 2: The mark indicates Short Lead Time Service applicable models. See p. 668 for details.


Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9RA0612P4J001 With pulse sensor with PWM control


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9RA0624P4J001 With pulse sensor with PWM control


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9RA0648P4J001 With pulse sensor with PWM control


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9RA0612J4001 With pulse sensor

Operating voltage range




9RA0612G4001 With pulse sensor

Operating voltage range




9RA0612S4001 With pulse sensor

Operating voltage range




9RA0612H4001 With pulse sensor

Operating voltage range




9RA0612F4001 With pulse sensor

Operating voltage range




9RA0612M4001 With pulse sensor

Operating voltage range




9RA0624J4001 With pulse sensor

Operating voltage range




9RA0624G4001 With pulse sensor

Operating voltage range




9RA0624S4001 With pulse sensor

Operating voltage range




9RA0624H4001 With pulse sensor

Operating voltage range




9RA0624F4001 With pulse sensor

Operating voltage range



9RA0624M4001 With pulse sensor


Operating voltage range



Airflow - Static Pressure Characteristics


9RA0648J4001 With pulse sensor

Operating voltage range




9RA0648G4001 With pulse sensor


Operating voltage range



Dimensions (unit: mm) (Ribbed frame with pulse sensor with PWM control)



Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)



Options

Finger guards

page: p. 598

Model no.: 109-139E, 109-139H

Resin finger guards

page: p. 605

Model no.: 109-1003G

Resin filter kits

page: p. 606

Model no.: 109-1003F13 (13PPI), 109-1003F20 (20PPI), 109-1003F30 (30PPI), 109-1003F40 (40PPI)